

This product raises the total alkalinity in swimming pool water. It boosts the effectiveness of your pool water disinfectant, as well as aids in the prevention of scale formation, metal corrosion and the etching of pool surfaces. It helps maintain your pool's pH level and eliminates pH "bounce". Easy to use and dissolves quickly.

DIRECTIONS

Test for total alkalinity with a reliable test kit. The desired range for total alkalinity is as follows:

Fiberglass Pools	70-100 ppm
Marcite, Painted, Tile, or Exposed Aggregate Pools	80-120 ppm
Vinyl Pools	120-140 ppm

If the total alkalinity is less than this desired range, add this product directly to the pool water while the pump is in operation, in accordance with the table below.

HOW TO INCREASE ALKALINTY

DESIRED INCREASE IN PPM	GALLONS IN POOL		
	5,000	10,000	20,000
10 ppm	11 oz.	1 lb. 6 oz.	2 lbs. 13 oz.
20 ppm	1 lb. 6 oz.	2 lbs. 13 oz.	5 lbs. 10 oz.
30 ppm	2 lbs. 2 oz.	4 lbs. 3 oz.	8 lbs. 6 oz.
40 ppm	2 lbs. 13 oz.	5 lbs. 10 oz.	11 lbs. 3 oz.
60 ppm	4 lbs. 3 oz.	8 lbs. 6 oz.	16 lbs. 13 oz.
80 ppm	5 lbs. 10 oz.	11 lbs. 3 oz.	22 lbs. 6 oz.
100 ppm	7 lbs.	14 lbs.	28 lbs.

FIRST AID

IF IN EYES: Flush eyes with water for 15 minutes, while lifting eyelids. Call a physician if irritation persists.

IF ON SKIN OR CLOTHING: Brush off excess and rinse skin with water.

IF INHALED: Remove to fresh air.

IF SWALLOWED: If large amounts are swallowed, drink a large quantity of water. Do not induce vomiting. Call a physician.

STORAGE AND DISPOSAL

Store closed container in a cool, dry, well-ventilated place. When container is empty, rinse thoroughly with water, wrap securely in newspaper and place in trash collection.

CA Reg. No. 53822-50006

Distributed By:
Robelle Industries, Inc.
60 Campanelli Drive
Braintree, MA 02184

www.robelleind.com

REV020624