

Helps prevent stains and discoloration from iron, copper, magnesium and other minerals.

# SUPER MINERAL AND STAIN ERASE

## ROBELLE

*everything for your swimming pool*

ITEM NO. 2555  
L9013FP

**OUR MOST  
CONCENTRATED  
MINERAL & STAIN  
PREVENTER!**

**KEEP OUT OF REACH OF CHILDREN**

See First Aid statement and other precautions on side panel.  
Read all instructions carefully before use.

## 1 QUART

### GENERAL INFORMATION

This product is specially designed to chelate complex minerals that naturally occur in some water supplies. Minerals, such as iron or manganese, can cause stains and discolored water.

Water that has been pre-treated with this product can avoid problems that can arise from the reaction of iron or manganese with subsequent additions of chlorine or shock treatment.

This product is concentrated and ready to use.

This product will not interfere with chlorine, algaecides, or stabilizers. Add separately and do not mix with other chemicals.

When used regularly, this product will help prevent scale build-up and mineral precipitation caused by other chemical additions.

### FIRST AID

Harmful if swallowed. May cause skin damage. Avoid contact with skin, eyes or clothing. In case of contact wash thoroughly with water. In case of eye contact, or if taken internally, seek medical attention.

### DIRECTIONS FOR USE NEW POOLS OR POOL OPENING

To prevent discoloration of the pool water due to trace amounts of IRON, MANGANESE, and other heavy metals, add 1 1/2 ounces for each 1000 gallons of pool water.

This addition should be made before any other chemicals are added. Recirculate the water, to insure uniform distribution, before proceeding with other chemical additions.

### DISCOLORED WATER

Have your dealer determine if the discoloration is due to IRON or MANGANESE. If the water contains less than 1 PPM of these materials, add 1 1/2 ounces for each 1000 gallons of pool water. If the water contains greater than 1 PPM add proportionately greater amounts.

Test the pH of the water, after addition, and adjust to 7.2-7.6, as necessary. Recirculate the water to insure uniform distribution.

### SCALE BUILD-UP

Scale build-up is due to high levels of calcium and other hardness minerals. Add 3/4 ounce for each 1000 gallons of pool water and recirculate for at least 6 hours after addition.

To prevent a recurrence of scale build-up, add 1-2 ounces for each 5000 gallons of pool water each week.

Distributed by:  
**Robelle Industries, Inc.**  
131 Tosca Drive  
Stoughton, MA 02072

[www.robelleind.com](http://www.robelleind.com)

REV123009



32 oz. \_\_\_\_

30 oz. \_\_\_\_

28 oz. \_\_\_\_

26 oz. \_\_\_\_

24 oz. \_\_\_\_

22 oz. \_\_\_\_

20 oz. \_\_\_\_

18 oz. \_\_\_\_

16 oz. \_\_\_\_

14 oz. \_\_\_\_

12 oz. \_\_\_\_

10 oz. \_\_\_\_

8 oz. \_\_\_\_

6 oz. \_\_\_\_

4 oz. \_\_\_\_

2 oz. \_\_\_\_